



HUBODOMETERS

Mechanical Hubodometers

Series 7777



“The Original Hubodometer”

The Time-Tested and Best Selling Distance Measuring Device

Features & Benefits

- Records every revolution in both directions
- Hermetically sealed diecast zinc case with inert gas and double o-ring protection
- Precision shaft supported front and rear with needle bearings
- Specified by revolution per mile/kilometer — not just tire size
- 300,000 mile/500,000 kilometer warranty (no time limit)
- Unique counterbalance design prevent orbiting — even on rough roads
- Magnifying crystal enlarge digits and angles up for easier reading

Specifications

Speed

1000 RPM, maximum

Warranty

300,000 miles or 500,000 kilometers

Size of Figures

0.187 in. (4.75mm) x 0.125 in. (3.18mm)

Color of Figures

Tenths wheel is red on white.
Other wheels are white on black

Mounting

0.500-20 UNF 2A threaded integral mounting stud

Construction

Case: Diecast zinc
Figure wheels, pinions and gears: acetal resin
Crystal: polycarbonate resin
Needle bearings: steel
Main shaft: hardened steel

PERFORMANCE WHEN IT COUNTS!

**V
R** VEEDER-ROOT

One Model For Any Tire Ever Made... Or Ever Will Be Made!

Features & Benefits

- **Drop Your Inventory**
Replace your bloated inventory with just one standard unit to handle all of your tires sizes. Digital electronic circuitry allows rapid and easy configuration anywhere, without need for a specialized programming instrument.
- **Error Free Display**
Large, high-contrast display always remains in upright position providing easy, reliable and highly accurate data collection
- **Extended Record Keeping**
Separate trip and lifetime totals permit specialized record keeping methods. Rite-Trak's setup features include capturing data as miles or kilometers.
- **Secure, Reliable Operation**
5 year warranty — no mileage limitation. Security features include serial number viewing via the display as well as tamperproof setup scheme. Only one moving part for increased reliability. Secure lockout feature. Changes to the unit's setup can be permanently disabled to prevent tampering. May be preset to any starting value.

Specifications

Display

LCD, 7 digits, 0.45" high (11.43mm)

Warranty

5 year — no mileage limitation

Mounting

0.500-20 UNF 2A threaded integral mounting stud

Construction

Case: Diecast zinc



Electronic Hubodometers Model RT1000-000

Performance When It Counts!



www.vr-hubodometer.com

2100 West Broad Street Elizabethtown, NC 28337
800.390.6405 or 910.862.2511
customer.service@sptech.com

VR06172016